

RXW-DCS3025

Desktop Call Station



Server-less Paging up to 30 Zones



Standard SIP Integration



External Music Collection



Easy Installation with PoE



Volume control & Emergency call button



Versatile Functionality with PA System



Main Features

This advanced and highly versatile console is engineered to support multiple installation configurations, including desktop, embedded, and wall-mounted* deployments, ensuring seamless integration into diverse operational environments.

Equipped with a 10.2-inch TFT LCD touch display and a high-resolution 13MP HD camera, the system delivers smooth and reliable two-way video intercom functionality. It also features a built-in 3W speaker, a unidirectional microphone for clear audio capture, and integrated Bluetooth connectivity, providing flexible and efficient communication options.

The console offers comprehensive broadcasting and communication capabilities, including zone-based paging and multiple intelligent calling modes such as keypad dialing, bookmark access, and map-based selection. Advanced facial recognition technology enhances security and access control, while support for pre-recorded message broadcasting and full-duplex audio/video conferencing ensures effective communication across all levels.

For system management, the device enables real-time network monitoring with instant status updates of all connected terminals. It is designed with relay input and output interfaces, allowing seamless integration with emergency systems such as panic buttons, alarm units, sensors,

The console supports the SIP protocol, ensuring full compatibility with leading VoIP platforms, enabling scalable, future-ready communication infrastructure

Technical Parameters

RXW-DCS3025	SIP Desktop Call Station
MAIN SCREEN	10.1-inch(1280x800)touch screen
HANDSET	1 nos Handset
PA FEATURE	Support SIP protocol for PA fetures
GOOSENECK MICROPHONE	1 nos gooseneck microphone
ETHERNET PORT	2 nos

RXW-DCS3025

Desktop Call Station



Technical Parameters

RXW-DCS3025	SIP Desktop Call Station
MAIN SCREEN	10.1-inch(1280x800)touch screen
HANDSET	1 nos Handset
PA FEATURE	Support SIP protocol for PA fetures
GOOSENECK MICROPHONE	1 nos gooseneck microphone
ETHERNET PORT	2 nos
USB PORT	1 nos
HDMI PORT	1 Nos
VOLUME CONTROL BUTTON	Volume control button
AUDIO CODEC	MP2, MP3, PCM, ADPCM
AUDIO SAMPLING & BIT	8kHz~48kHz, 16bit/32bit, 8kbps~320kbps
FREQUENCY RESPONSE	22Hz~20KHz
VIDEO CALL	Supported
VIDEO FEATURE	Video callresolution upto 13MP Imageformat:JPEG/PNG/BMP & Video format:MP4 Bandwidth selection: 512kbps~4Mbps 13 MP camera adjustment camera
PROTOCOL	SIP2.0 ,overUDP/TCP/TLS, RTP/RTCP/ SRTP, STUN ,DHCP, HTTP/HTTPS
POWER	POE & External power supply
ANNOUCEMENT FEATURES	Group announcement , Zone wise Announcement Back ground music announcement Schedule Announcement ,Pre recorded message play
GIGABIT ETHERNET	Adaptive 10/100/1000Mbps network port providing high-speed network transmission.
SAFETY LOCK	Safety Keyhole x1
POWER SUPPLY	DC12V/3.3A , POE(IEEE802.3af
POWER CONSUMPTION	≤20W
RELATIVE HUMIDITY	≤90% RH non-condensing
COLOR	Dark Gray/Black*
CERTIFICATIONS	CE ,FCC,ROHS

Disclaimer: As per our company policy one of the constant product improvements the right is there for reserved to modify the product specification on without prior notice and the picture shown in the datasheet is a design base, the actual picture may vary.